

COD-F40

Ford F150 & Raptor OEM Camera Controller NTV-KIT929





Moni 01/29/2021 NTV-DOC342

Overview

The COD-F40 (Camera-On-Demand) kit allows 2016+ Ford F150 and Raptor trucks equipped with OEM single camera *or* surround view cameras (4-camera system) to be displayed on demand, without lock-out restrictions. Additional features include easy force rear-cam/front cam and Navigation control in motion. *NOTE: This kit <u>will NOT program any camera system</u>. This module is only intended for use with trucks equipped with at least one OEM camera.*



Pin #	Description	Color
1	12v Constant Power (+)	Yellow
2	INPUT 1: NOT USED	Red
3	INPUT 2: NOT USED	Blue
4	INPUT 3: NOT USED	Pink
5	RX (OE camera button – button side)	Blue
6	CAN-3 HIGH (camera module)	Blue
7	CAN-2 HIGH (CAN gateway)	Blue
8	CAN-1 HIGH (APIM)	Yellow
9	CAN-0 HIGH (CAN gateway)	Yellow/Black
10	Ground (-)	Black
11	OUTPUT 1: NOT USED	White/Red
12	OUTPUT 2: NOT USED	White/Blue
13	OUTPUT 3: NOT USED	White/Purple
14	TX (OE camera button – module side)	Purple
15	CAN-3 LOW (camera module)	Purple
16	CAN-2 LOW (CAN gateway)	Purple
17	CAN-1 LOW (APIM)	Orange
18	CAN-0 LOW (CAN gateway)	Orange/White

Agreement: End user agrees to use this product in compliance with all State and Federal laws. NAV-TV Corp. would not be held liable for misuse of its product. If you do not agree, please discontinue use immediately and return product to place of purchase. This product is intended for off-road use and passenger entertainment only.


COD-F40 Installation

- 1. Remove the 8" SYNC 3 screen (radio):
 - a. Remove the center channel speaker cover (if equipped) on the top (middle) of the dash (4 clips only) NOTE: this panel is very tight.
 - b. Remove (2) 7mm bolts securing the top panel (previously hidden by the speaker grill).
 - c. Remove the whole upper shelf panel, it should be held in by clips only, now. Disconnect the speaker lead. Set this panel assembly aside.

- d. Remove (2) 7mm screws on top of the climate/screen dash panel, and then pull panel straight towards you. Disconnect all harnesses and set the panel aside.
- e. Remove (6) 7mm screws securing the screen (APIM) to the sub-dash. Disconnect all harnesses and set the APIM aside.

Agreement: End user agrees to use this product in compliance with all State and Federal laws. NAV-TV Corp. would not be held liable for misuse of its product. If you do not agree, please discontinue use immediately and return product to place of purchase. This product is intended for off-road use and passenger entertainment only.







Moni 01/29/2021 NTV-DOC34



SAT-switcher board

0

- 2. Connect the provided (large, main) T-Harness between the vehicle harness and the APIM (screen).
- 3. Connect the provided SAT-switcher board/harness to the IPM M(directly behind screen, see below for variants). Connect the (OE) IPM vehicle harness (previously removed 20-pin) to the SAT-switcher board.

- 4. Connect the 8-pin harness from the main *T-Harness* to the SATswitcher board's 8-pin port.
- 5. Connect the 18-pin plug to the COD module and secure it to the sub-dash (up underneath the center-channel speaker) so that nothing rattles. NOTE: No other wires from the main unit are used for this installation.
- 6. Return the screen to the sub-dash and reconnect the climate/screen surround panel for testing.


Agreement: End user agrees to use this product in compliance with all State and Federal laws. NAV-TV Corp. would not be held liable for misuse of

7. Proceed to 'COD-F40 Operation'.

use and passenger entertainment only.










IPM (camera module): Single OEM

\

Moni 01/29/2021 NTV-DOC34



Agreement: End user agrees to use this product in compliance with all State and Federal laws. NAV-TV Corp. would not be held liable for misuse of its product. If you do not agree, please discontinue use immediately and return product to place of purchase. This product is intended for off-road use and passenger entertainment only.

COD-F40 Operation

Camera Button

Once the COD-F40 module is connected properly, all added camera commands are performed through the factory camera button. Added features are outlined below:

Press the camera button ONCE to enter rear view modes.

- Press the camera button TWICE (double click) to enter front view modes.
- While in Front or Rear camera modes, any additional Camera press will advance the screen to the next view (360>Full>Panoramic)
- Press and HOLD the button to clear out to the OEM menu at any time of rear camera or front camera operations.
- The cameras will no longer lock out





*NOTE: forcing the **rear camera** may affect NAV guidance temporarily. This is a factory limitation.

Agreement: End user agrees to use this product in compliance with all State and Federal laws. NAV-TV Corp. would not be held liable for misuse of its product. If you do not agree, please discontinue use immediately and return product to place of purchase. This product is intended for off-road use and passenger entertainment only.

COD-F40 NOTES

- SYNC 3 radio must be at least Version 3.0 for all features to work properly. Under SETTINGS, then GENERAL SETTINGS, look for the SYNC version. The radio system can be updated over the air if the vehicle is connected to a local WiFi connection. For more detail information, watch this video: <u>https://www.youtube.com/watch?v=No8fJ7V21Y8</u>
- If you suspect the COD module needs a software update, connect it to a Windows PC via USB (mini) cable and go to <u>www.navtvdevice.com</u>. All updates are available here.



Agreement: End user agrees to use this product in compliance with all State and Federal laws. NAV-TV Corp. would not be held liable for misuse of its product. If you do not agree, please discontinue use immediately and return product to place of purchase. This product is intended for off-road use and passenger entertainment only.